

RAYPA

Vertical autoclaves with drying

AE-DRY Series **CLASSIC LINE**

Technical information



Why choose RAYPA?

Expert manufacturer, original design,
global brand



GLOBAL REACH

With half a century of experience, we have a long list of satisfied customers around the world. Currently, we export 85% of our annual turnover and have a stable network of distributors with presence in over 100 countries.



EFFICIENT TECHNICAL SERVICE

Our team of highly qualified technicians and engineers is expert in our products. If you experience a technical issue, it will be our priority to rectify it. When you purchase a RAYPA unit, you're guaranteed top-level support and technical assistance.



EXPERT MANUFACTURER

After more than 50 years in the industry, RAYPA is a global leader in the manufacture of laboratory autoclaves. Each of our autoclaves is designed and manufactured entirely within our modern facility equipped with the latest technology.



FULL AND CUSTOMIZABLE RANGE

We offer an extensive portfolio of laboratory autoclaves to cover multiple applications and market segments. Discover the combination of autoclave model and accessories that best fits your needs within our 11 series and 35 available models.



INNOVATION AND QUALITY

Our products feature advanced technology, ongoing innovation, superior construction quality, and are designed for a long service life. Our technical and engineering staff works tirelessly every day to optimize our products and exceed our customers' expectations.



COMPREHENSIVE CONSULTANCY

Our team of specialists assesses each project and provides guidance to clients on the option that best suits their requirements. After the sale, we offer training on the use and recommended maintenance of each unit to ensure its optimal operation and extend its lifespan.

Vertical autoclaves with drying

AE-DRY Series vertical floor-standing autoclaves with top-loading access cover most laboratory sterilization needs in many industries, educational institutions and research facilities with the aim of increasing the productivity of the laboratory. With a spacious chamber, the vacuum drying function and the integrated water tank, along an optimized use of resources like water, energy, and time, these autoclaves provide an efficient and cost-effective solution to handle laboratory workloads effectively.

RECOMMENDED APPLICATIONS

-  Culture media and liquids
-  Glassware
-  Plastics and metal objects
-  Laboratory waste bags
-  Porous solids and wrapped objects*

*For this application, the sterilization time must be extended, the chamber should not be fully loaded, and chemical and/or biological tests should be used to validate the proper sterilization of the load.



AE-DRY Series

MAIN FEATURES

COST-EFFECTIVE SOLUTION

AE-DRY Series autoclaves are robust and offer excellent performance for liquids and solids sterilization procedures. The final vacuum drying feature by a heating jacket and a vacuum pump at the end of the sterilization cycle eliminates the need of an external equipment to dry the load, significantly reducing the duration of each sterilization procedure rotation and saving operator time.

MULTIPLE TYPES OF STERILIZATION

Several options available to perform sterilization of solids or liquids. Programmable final vacuum drying for the sterilization of solids, initial prevacuum for the sterilization of items of complex geometries and programmable temperature holding at the end of the cycle for the sterilization of culture media. Additionally, an optional flexible temperature probe is available for precise liquid sterilization.

EASY INSTALLATION AND MAINTENANCE

AE-DRY Series autoclaves are plug and play devices, requiring no special installation connections. They operate with just an electrical connection and can function without a drain. Each unit features an integrated water tank that automatically supplies the sterilization chamber, which is manually filled. For added convenience, an optional upgrade allows full automation of water supply directly from a water network. All models are equipped with casters, enabling easy mobility and use in different locations.

SAFETY FIRST

AE-DRY Series autoclaves are designed with several features to ensure the safety of the operators. These include an overpressure safety valve, a thermally insulated door, an overtemperature safety thermostat, a water level sensor, an open door detection system and an independent safety pneumatic system that locks the main door while positive pressure is present in the sterilization chamber.

ADVANTAGES



Equipped with heating jacket and vacuum pump to obtain a completely dry load at the end of a solids program.



The sterilization chamber and door are made of high-quality AISI-316L stainless steel, providing exceptional resistance to corrosion.



Autoclaves manufactured in full compliance with all applicable European Union quality, regulatory and safety standards.



Steam generation by powerful Incoloy® 825 electric heating elements assembled inside the sterilization chamber and shielded by a protective grid.



Control by a PID microprocessor with 4 predefined and 6 editable programs, adjustable by time, temperature, drying time and type of sterilization cycle (solids or liquids, with optional agar mode and/or flexible temperature probe control).



Available special models with increased heating capacity to achieve faster heating and sterilization phases.



Suitable to sterilize wrapped and unwrapped loads, small porous and hollow objects and items of complex geometries with cavities thanks to the standard initial prevacuum phase.



Automatic water supply from the integrated water tank to the sterilization chamber, with water level sensors at both locations. Optional upgrade for automatic supply from a water network.



Adjustable temperature holding at the end of the sterilization cycle between 40-80°C (agar mode).



Programmable auto-start for up to 24h.



Plug and play equipment, no plumbing required.



Seamless mobility, all models include casters.



Optional software for sterilization data management.



Optional embedded or external printer.

WORKING PRINCIPLE

AE-DRY Series autoclaves provide a solution for the multiple sterilization needs of a general laboratory, including glassware, plastics, metal utensils, laboratory waste bags, wrapped and unwrapped loads, small porous and hollow objects, liquids, culture media, and other laboratory items.

The load has to be placed in baskets inside the chamber, and after manually filling the independent clean water tank with purified water, the equipment starts to create the initial prevacuum, automatically supplies water to the sterilization chamber, heats up and purges until the pre-programmed combination of sterilization time and temperature is reached.



*Standard casters included. Optional: medical-grade casters with brakes (Ref. 4WHBR).

OPERATION OF A STERILIZATION CYCLE FOR SOLID LOADS

PREVACUUM PHASE

- In this initial step, the equipment's vacuum pump mechanically removes air from the chamber and load through a single vacuum pulse of -0,75 Bargs. This allows the steam to penetrate load objects of difficult geometries.
- Afterwards, the independent water tank starts to supply water to the sterilization chamber.

HEATING PHASE

- After completing the prevacuum phase and once the sterilization chamber bottom is filled with water, the powerful heating elements assembled at the bottom of the sterilization chamber heat up dramatically, transferring energy to water to produce saturated steam throughout the chamber.
- To shorten the duration of this step, RAYPA offers special models with increased heating capacity, a feature of particular interest for autoclaves operating in laboratories with high workloads.

STERILIZATION PHASE



- Upon reaching the set sterilization temperature inside the chamber, the sterilization phase begins accurately sustaining the temperature throughout the duration of this phase.
- This crucial step is controlled by a PT-100 Class A temperature probe located within the chamber. As an option for liquids sterilization processes, this phase can be regulated by a flexible PT-100 Class A temperature probe located inside a sample.

VACUUM DRYING PHASE

- Once the sterilization phase is completed, only in solids programs, a vacuum drying phase begins, in which multiple vacuum pulses are produced by means of a vacuum pump and heating jacket to completely dry the load. The water is automatically returned to the integrated water tank.

COOLING PHASE

- Finally, a natural cooling phase begins. A beep will sound when a safe temperature is reached allowing the chamber to be opened.
- In liquid programs with agar mode, the preprogrammed temperature (selectable between 40°C and 80°C) will be maintained indefinitely.



PREDEFINED PROGRAMS

Program N°	Sterilization temperature °C	Sterilization time min	Drying time min	Program mode
P0	115	60	12	Solids
P1	121	30	25	Solids
P2	133	20	30	Solids
P3	121	20	-	Liquids

AE-DRY Series autoclaves have 10 programs, from P0 to P9, and the first four are predefined and protected.

The remaining programs from P4 to P9, can be edited by setting the following parameters:

- Sterilization temperature.
- Sterilization time.
- Final drying time.
- Sterilization mode (solids or liquids)
- Sterilization with temperature maintenance at the end of the cycle (agar mode).
- Temperature control of the sterilization cycle can be performed by the chamber temperature probe or by the combined use of the chamber probe and the flexible probe.

DIGITAL MICROPROCESSOR

Digital PID microprocessor with 6 push-buttons for simple programming and parameter selection.



FUNCTIONS OF THE DISPLAY

The alphanumeric screen apart from showing the standard sterilization parameters also shows current sterilization phase and several visual alerts, including warning or failure messages. The available languages include English, Spanish, French and Catalan. To install other languages, please contact us.



AE-DRY Series

LOADING CAPACITIES



ISO ERLLENMEYER FLASKS

Autoclave model	Usable volume L	250mL (Ø85 x 143mm)				500mL (Ø105 x 183mm)				1000mL (Ø131 x 230mm)				2000mL (Ø166 x 280mm)			
		Total baskets	Units / basket	Total units		Total baskets	Units / basket	Total units		Total baskets	Units / basket	Total units		Total baskets	Units / basket	Total units	
				A	B			A	B			A	B			A	B
AE-28-DRY	31	2	7	14	=	1	4	4	8	1	1	1	=	1	1	1	=
AE-50-DRY	50	3	7	21	28	1	4	4	12	1	1	1	=	1	1	1	2
AE-75-DRY	75	3	12	36	=	2	8	16	24	2	5	10	=	1	3	3	6
AE-110-DRY	110	4	12	48	60	3	8	24	32	3	5	15	=	1	3	3	6
AE-150-DRY	153	4	21	84	105	4	14	56	=	3	8	24	=	1	5	5	10

A: Number of units using standard baskets.

B: Number of units using specially designed baskets for the specific combination of autoclave model and container.



ISO BOTTLES

Autoclave model	Usable volume L	250mL (Ø70 x 143mm)				500mL (Ø80 x 185mm)				1000mL (Ø101 x 230mm)				2000mL (Ø136 x 260mm)			
		Total baskets	Units / basket	Total units		Total baskets	Units / basket	Total units		Total baskets	Units / basket	Total units		Total baskets	Units / basket	Total units	
				A	B			A	B			A	B			A	B
AE-28-DRY	31	2	9	18	=	1	7	7	14	1	4	4	=	1	1	1	=
AE-50-DRY	50	3	9	27	36	1	7	7	21	1	4	4	=	1	1	1	2
AE-75-DRY	75	3	20	60	=	2	14	28	42	2	8	16	=	1	4	4	8
AE-110-DRY	110	4	20	80	100	3	14	42	56	3	8	24	=	1	4	4	12
AE-150-DRY	153	4	33	132	165	4	24	96	=	3	15	45	=	1	8	8	16

A: Number of units using standard baskets.

B: Number of units using specially designed baskets for the specific combination of autoclave model and container.

The data contained within these tables, regarding load capacities, serves as a non-binding guide to assist you in the selection of the most appropriate autoclave model.

ACCESSORIES

INTEGRATED BASKET LIFT SYSTEM

References		CLASSIC-LIFT	CLASSIC-LIFT-R
Dimensions L x D x H mm		800 x 300 x 2100	800 x 300 x 2600
Power W		480	480
Voltage V		230	230
Frequency Hz		50/60	50/60
Weight Kg		40	45
Maximum load Kg		30	40
For autoclaves with the following chamber volumes	79 L	✓	-
	115 L	✓	✓
	175 L	-	✓

- Stainless steel electric lift system built into the side of the autoclave with swivel arm to help load and unload heavy items. Push-button operation with opening up to 200°
- Motor with auto brake system in the event of obstacles or overload.
- Available in two models: the standard lift system and reinforced lift system.
- It can be factory fitted or retrofitted.



Download technical data sheet

MOBILE BASKET LIFT SYSTEM

Reference	MOB-LIFT
Dimensions L x D x H mm	420 x 800 x 2200
Power W	200
Voltage V	115 - 230
Frequency Hz	50/60
Weight Kg	85
Maximum load Kg	30

- Stainless steel electric lift system with casters to help load and unload heavy items up to 30Kg.
- Equipped with long-life battery for cordless use.
- Push-button operation.
- Motor with auto brake system in the event of obstacles or overload.
- Compatible with any autoclave model.



Download technical data sheet

AE-DRY Series

ACCESSORIES

STAINLESS STEEL WIRE BASKETS FOR STERILIZING CLEAN LOADS OR HEAVY ITEMS

References		CV-28	CV-75-130	CV-75S	CV-75	CV-150-130	CV-150S	CV-150M
Dimensions	External Ø x H mm	270 x 185	370 x 130	370 x 180	370 x 265	470 x 130	470 x 190	470 x 235
	Internal Ø x H mm	260 x 180	360 x 125	360 x 175	360 x 260	460 x 125	460 x 185	460 x 230
Maximum capacity for autoclaves with the following chamber volumes	33 L	2	-	-	-	-	-	-
	55 L	3	-	-	-	-	-	-
	79 L	-	4	3	2	-	-	-
	115 L	-	6	4	3	-	-	-
	175 L	-	-	-	-	6	4	3



STAINLESS STEEL LIQUIDS COLLECTOR TRAY FOR WIRE BASKETS

References		TR-270	TR-370	TR-470
Dimensions	External Ø x H mm	240 x 50	320 x 50	420 x 50
	Internal Ø x H mm	238 x 48	318 x 48	418 x 48
For the following wire baskets models	CV-28	✓	-	-
	CV-75S & CV-75	-	✓	-
	CV-150S & CV-150M	-	-	✓



UNPERFORATED STAINLESS STEEL BASKETS FOR STERILIZING DIRTY LOADS OR OBJECTS WITH RISK OF SPILLAGE

References		CCI-28	CCI-75S	CCI-75	CCI-150S	CCI-150M
Dimensions	External Ø x H mm	270 x 185	370 x 180	370 x 265	470 x 190	470 x 235
	Internal Ø x H mm	260 x 180	360 x 175	360 x 260	460 x 185	460 x 230
Maximum capacity for autoclaves with the following chamber volumes	33 L	2	-	-	-	-
	55 L	3	-	-	-	-
	79 L	-	3	2	-	-
	115 L	-	4	3	-	-
	175 L	-	-	-	4	3



STAINLESS STEEL "SCHIMMELBUSCH" DRUM FOR STERILIZING INSTRUMENTS AND BIOHAZARDOUS LOADS

References		TBE-24x16	TBE-34x24	TBE-48x24
Dimensions	External Ø x H mm	240 x 165	340 x 240	480 x 240
	Internal Ø x H mm	230 x 155	330 x 230	470 x 230
Maximum capacity for autoclaves with the following chamber volumes	33 L	2	-	-
	55 L	4	-	-
	79 L	-	2	-
	115 L	-	3	-
	175 L	-	-	3



ACCESSORIES

STAINLESS STEEL CYLINDERS FOR STERILIZING PETRI DISHES

References		CEP-1027	CEP-1041	CEP-1427	CEP-1441
Dimensions	External Ø x H mm	100 x 270	100 x 410	140 x 270	140 x 410
Petri dishes	Maximum number dishes / cylinder	10	18	10	18
	Diameter Ø mm	80	80	120	120
Maximum capacity for autoclaves with the following chamber volumes	33 L	4	4	2	2
	55 L	8	4	4	2
	79 L	16	8	10	5
	115 L	24	16	15	10
	175 L	28	14	16	8



STAINLESS STEEL CYLINDERS FOR STERILIZING PIPETTES

References		CEPP-726	CEPP-740	CEPP-1025	CEPP-1435
Dimensions	External Ø x H mm	70 x 260	70 x 400	100 x 250	140 x 350
	Internal Ø x H mm	60 x 250	60 x 390	90 x 240	130 x 340
Maximum capacity for autoclaves with the following chamber volumes	33 L	11	11	6	6
	55 L	22	11	12	12
	79 L	42	21	20	10
	115 L	63	42	30	20
	175 L	90	30	51	34



STAINLESS STEEL WIRE BASKET WITH HEIGHT ADJUSTABLE TRAYS

References		SRA-R-300	SRA-R-400	SRA-R-500
External dimensions Ø x H mm		250 x 190	350 x 180	450 x 180
Trays	References	TRAY-SRA-R-300	TRAY-SRA-R-400	TRAY-SRA-R-500
	Dimensions Ø x H mm	240 x 20	340 x 20	440 x 20
Maximum capacity for autoclaves with the following chamber volumes	33 L	2	-	-
	55 L	3	-	-
	79 L	-	3	-
	115 L	-	4	-
	175 L	-	-	4

*The purchase of a tray support comes with a set of two trays and six fastening clips. Likewise, the purchase of a tray includes a set of three fastening clips.

- For sterilization of instruments, small bags and other small objects that must be placed straight up.
- Material: AISI-304 stainless steel.



ACCESSORIES



FLEXIBLE TEMPERATURE PROBE PT-100 CLASS A

After installing this accessory, the temperature regulation of the sterilization cycle can either be controlled by the main chamber temperature probe or both the main chamber temperature probe and the flexible temperature probe.

The temperature control by the flexible temperature probe is especially advantageous for processes involving the sterilization of large volumes of liquids, where the sterilization process is regulated by both the temperature achieved in the center of the liquid sample as well as the temperature achieved in the sterilization chamber. Furthermore, should the autoclave be opened at chamber temperatures higher than 80°C there is a risk of liquids boiling over which can be avoided if the temperature of the sample is controlled throughout the sterilization procedure. Must be installed in our facilities.

Ref. PT-2

[Download technical data sheet](#)



EXTERNAL DOT MATRIX PRINTER

Prints program number, cycle number, temperature, pressure, date and hour and error messages.

Selectable print frequency between 10 and 240 seconds.

Connection: RS-232.

Ref. ITS

Consumables: PAPER-ITS for paper and 70945 for ribbon.

[Download technical data sheet](#)



EMBEDDED THERMAL PRINTER

Prints program number, cycle number, temperature, pressure, date and hour of the run and error messages.


Selectable print frequency between 10 and 240 seconds.

Must be installed at our factory.

Ref. IT

Consumable: PAPER-IT for paper

[Download technical data sheet](#)




SOFTWARE SW7000

Communication software between the equipment and the PC for display and recording in real time or display after each cycle. Cycles can also be printed or exported to Excel.

PC connection via RS-232.

It is supplied with an RS-232 cable, a USB memory stick including installation software and drivers, and an RS-232 to USB adapter.

Ref. SW7000



CABLE GLAND

Installation of a Ø2mm or Ø4mm cable gland to provide access to as many as 8 external temperature probes for calibration and validation procedures.

Ref. CG2MM & CG4MM

[Download technical data sheet](#)

ACCESSORIES



EXTERNAL TEMPERATURE PROBE ADAPTER

External adapter for continuous validation processes that provides access to an external probe (Ø3-6mm) to take temperature readings that are independent of the equipment microprocessor.

It is located on the autoclave door.

Must be installed at our factory.

Ref. EXT-TP



[Download technical data sheet](#)



TRANSPORT TROLLEY

Auxiliary trolley to aid in the loading and unloading of the autoclave.

Made of chrome iron and plastic.

The surface of each shelf is textured to prevent the load from moving.

Equipped with rubber casters to reduce noise and prevent floor wear.

Dimensions (LxDxH): 730x490x700mm

Ref. TR-TR



[Download technical data sheet](#)



PREMIUM CASTERS

Although all AE-DRY Series autoclaves include casters, this accessory offers the option of upgrading to stronger, medical grade casters that include brakes.

This enhances the mobility of the equipment.

Must be installed at our factory.

Ref. 4WHBR



ECO-EFFICIENT WATER PURIFIER

Eco-efficient direct-flow water purifier with LED display and no accumulation of water. Capable of filtering 1,3L/min.

The installation of this accessory requires the joint installation of the external tank (TANK-KLL) and the automatic water filling system (KLL).

Ref. ECOPUR-500



[Download technical data sheet](#)



PURIFIED WATER TANK

Alternative solution for the storage of up to 25L of purified water in the absence of a water network.

Ref. TANK-KLL



[Download technical data sheet](#)



AUTOMATIC WATER FILLING KIT

Water pump for automating the supply of purified water to the integrated water tank.

Compatible with installations with a purified water network or a purified water tank, or installations with a non purified water network; in the latter case, a water purifier (ECOPUR-500) and a purified water tank (TANK-KLL) will be required.

Must be installed at our factory.

Ref. KLL



[Download technical data sheet](#)

ACCESSORIES



TEMPERATURE DATA LOGGER

AISI-316L stainless steel disk temperature recorder with connection base and software.
Recommended for autoclave validation and for monitoring the internal temperature of containers.
Available in different sizes.

Ref. BDL-DISK3618_CL



[Download technical data sheet](#)



STERILIZATION CONTROL TAPE

Class 1 indicator for steam sterilization. The color change indicates that the materials have been processed; however, this does not guarantee adequate sterilization. Additional methods, such as biological indicators (EN ISO 11138), are required.

Pack of 5 rolls of 50m x 19mm tape.

Ref. TEST-CT



[Download technical data sheet](#)



INTERNAL RADIAL FAN

Optimize and reduce cooling time, ensuring greater efficiency in sterilization processes.

Must be installed in our facilities.

Ref. AIRCOOL-V



[Download technical data sheet](#)

SPECIFIC SERVICES



IQ-OQ DOCUMENTATION

Delivery of documentation and protocols for autoclave qualification through a third party.

Ref. IQ-OQ DOC



[Download technical data sheet](#)



IQ-OQ-PQ QUALIFICATION

Autoclave qualification service performed by RAYPA technicians or authorized entities. It covers the startup of the equipment and the comprehensive qualification of its performance.

Ref. IQ-OQ-PQ



[Download technical data sheet](#)



CALIBRATION CERTIFICATE FOLLOWING ENAC TRACEABILITY STANDARDS

Unitary certification of proper equipment calibration and performance in compliance with international standards.

Ref. MAPEO-ENAC



MAPPING OF STABILITY AND HOMOGENEITY

Generation of documentary evidence certifying that the temperature and pressure distribution within the autoclave is uniform and stable, in accordance with the manufacturer's design specifications.

Ref. MAP-3, MAP-7 and MAP-9




ON-SITE COMMISSIONING & TRAINING

On-site commissioning, which includes verification of the correct operation and installation of the equipment and a training session for users on the use and maintenance of the equipment.

Ref. INSAE



[Download technical data sheet](#)



REMOTE COMMISSIONING & TRAINING

Guided remote startup including a training session for users on the operation and maintenance of the equipment.

Ref. INSAE-REM



[Download technical data sheet](#)



MAINTENANCE CONTRACT

Regular inspection plan that includes technical inspection, probe calibration and compliance with the preventive maintenance plan, in addition to tariff discounts.


Ref. MANT-1.2 and MANT-1.3



EXTENDED WARRANTY

Extended warranty up to a total of 3 years.


Ref. WE-CL



SET OF CONSUMABLES, SPARE PARTS AND ESSENTIAL COMPONENTS

Set of original spare parts, consumables and components, chosen specifically to adhere to each model's maintenance plan, intended to maximize equipment longevity and minimize downtime in the event of a malfunction.

TECHNICAL DRAWINGS OF THE AUTOCLAVE




MODELS

MODELS	L LENGTH with closed door	L1 LENGTH with maximum door opening	D DEPTH	H HEIGHT	HL LOAD HEIGHT
AE-28-DRY	505 mm	900 mm	580 mm	1110 mm	788 mm
AE-50-DRY	505 mm	900 mm	580 mm	1290 mm	967 mm
AE-75-DRY	610 mm	1100 mm	700 mm	1185 mm	862 mm
AE-110-DRY	610 mm	1100 mm	700 mm	1435 mm	1112 mm
AE-150-DRY	750 mm	1380 mm	820 mm	1400 mm	1073 mm

CONNECTIONS

1	Sterilization chamber electrical heating elements safety thermostat	7	Independent clean water tank overflow outlet
2	Heating jacket safety thermostat	8	Access to the drain filter and sterilization chamber drain outlet
3	Power supply cable (AE-110-DRY and AE-150-DRY models)	9	RS-232 Port
4	Safety valve outlet	10	Ethernet Port
5	Automatic water supply inlet	11	Power supply cable (AE-28-DRY, AE-50-DRY y AE-75-DRY models)
6	Independent clean water tank drain outlet		

TECHNICAL DRAWINGS OF THE AUTOCLAVE + CLASSIC-LIFT




MODEL OF BASKET LIFT SYSTEM	DIMENSIONS OF BASKET LIFT SYSTEM L x D x H	AUTOCLAVE MODELS	DIMENSIONS OF BASKET LIFT SYSTEM + AUTOCLAVE La x Da x Ha
CLASSIC-LIFT	800 x 300 x 2100 mm	AE-75-DRY	1276 x 1296 x 2100 mm
		AE-110-DRY	1276 x 1296 x 2600 mm
CLASSIC-LIFT-R	800 x 300 x 2600 mm	AE-150-DRY	1543 x 1536 x 2600 mm

TECHNICAL SUMMARY

	General classification	Recommended setting	General laboratory
		Equipment placement	Floor-standing
		Load direction	Top-loading
		Chamber profile	Round
	Recommended type of load	Glassware	++
		Culture media and liquids	++
		Laboratory waste bags	++
		Porous solids and wrapped loads	+
	Sterilization technology	Method to generate steam	Heating elements
		Type of purge	Vacuum
		Vacuum drying by heating jacket and vacuum pump	✓
	Transfer of data	RS-232	✓
	Batch printers	Embedded printer	0
		External printer	0
	Sterilization chamber and door specifications	Sterilization chamber volume	33 - 175 L
		External building material	AISI-304
		Sterilization chamber material	AISI-316L
		Heating elements material	Incoloy® 825
		Gasket material	Silicone rubber
		Min. - max. sterilization temperature	100 - 134 °C
		Maximum pressure (above atmospheric pressure)	2,1 Barg
		Mechanism to open the door	Manual wheel
		Direction in which the door opens	Lateral
		Automatic locking with pressure	✓
	User interface and microprocessor	Thermally insulated door	✓
		Screen display	Digital LCD
		Screen size	2 lines x 16 digits
		Total number of available programs	10
		Automatic microprocessor control	✓
	Special cycles and process optimization	Timer start	✓
		Agar mode (temperature holding after cycle ends 40-80°C)	✓
		Final postvacuum drying (to completely dry solid loads)	✓
	Adjustable cycle parameters	Temperature regulation by flexible probe	0
		Agar mode	40 - 80 °C
		Sterilization phase temperature	100 - 134 °C
		Duration of sterilization phase	1 - 250 min
		Duration of drying phase	3 - 99 min
		Temperature regulation by flexible probe	On/Off
		Sterilization mode (solids or liquids)	✓
	Other specifications	Air intake with bacteriological filter	✓
		Independent water tank capacity	9 - 20 L
		Flexible temperature probe	0
		Standard casters	✓
		Premium casters with brakes	0
		Pressure gauge	✓
		Electric customization (115-230M V / 230-400T V)	0
	Services	Special models with increased heating capacity	0
		Third-party qualification (IQ-OQ-PQ)	0

++ Recommended ✓ Standard 0 Optional

TECHNICAL DATA



Specifications

References	AE-28-DRY	AE-50-DRY	AE-75-DRY	AE-110-DRY	AE-150-DRY
Total/usable volume of the chamber L	33/31	55/50	79/75	115/110	175/153
Usable dimensions of the chamber Ø x H mm	300 x 440	300 x 710	400 x 600	400 x 850	500 x 760
External dimensions L x D x H mm	505 x 580 x 1110	505 x 580 x 1290	610 x 700 x 1185	610 x 700 x 1435	750 x 820 x 1400
Loading height mm	795	975	870	1120	1085
Net weight Kg	75	95	123	150	235
Available heating capacities W	2000 or 2800	2800 or 5000	3200 or 6000	4500, 6000 or 9000	6000 or 9000
Standard voltage* V	230	230	230	400	400
Frequency Hz	50/60	50/60	50/60	50/60	50/60

*Other voltages and electrical configurations available on request. Special models with increased heating capacity may operate with other voltages.

Safety features

- Safety valve.
- Safety thermostats with manual rearm for the heating jacket and the heating elements.
- Pneumatic door blocking system while positive pressure exists inside the sterilization chamber.
- Open door sensor.
- Thermally insulated door.
- Water level detector in the sterilization chamber.
- Water level detector (min./max.) in the independent water tank.
- Bacteriological filter for inlet air.
- Heating elements cover.
- Several visual and acoustic safety and warning alarms.

Regulations

All our AE-DRY Series autoclaves are designed to comply with the strictest international directives and standards, including the following regulations:

- **EN-61010-1** Safety requirements for electrical equipment for measurement, control and laboratory use. **Part 1:** General requirements.
- **EN-61010-2-040 Part 2-040:** Requirements for laboratory autoclaves.
- **EN-61326** Electrical equipment for measurement, control and laboratory use. EMC requirements.
- **AD 2000 Merkblatt** Pressure vessels.
- **2014/35/UE** Low voltage.
- **2014/30/UE** Electromagnetic compatibility.
- **2014/68/UE** Pressure equipment.

General features

Adjustable sterilization temperature	100 - 134 °C
Adjustable sterilization time	1 - 250 min
Adjustable drying time	3 - 99 min
Max. pressure	2,1 Barg
Sterilization control system	Fully automatic microprocessor control by either chamber temperature probe or flexible temperature probe
Air purge system	Mechanical displacement by vacuum pump
Vacuum drying system	Vacuum pump plus heating jacket
External building material	AISI-304 stainless steel
Sterilization chamber material	AISI-316L stainless steel
Heating elements material	Incoloy®825
Gasket material	Silicone rubber
Connection to PC	RS-232
Connection to printer	RS-232 or embedded
Number of programs	10 (4 preset and 6 user free)
Programmable auto-start	Up to 24h
Screen type	LCD display
Opening door mode	Horizontal swiveling door with blocking wheel
Monitoring of sterilization parameters	Self-control of obtained values (T° & t) vs programmed values. Cycle is automatically interrupted if obtained values differ from programmed values
Pressure display	Pressure gauge on control panel
Water management	Independent manually fed water tank that automatically supplies the sterilization chamber. Water returns automatically to the independent water tank after completing the sterilization phase. Optional upgrade for full automation of water supply directly from a water network
Drainage system	A drainage connection and a manual valve for overflow and drainage of the independent water tank and a screw to manually clean the drainage filter and drain the sterilization chamber
Casters	Included standard casters. Optional upgrade to medical grade casters with brakes

MORE INFORMATION

 Watch video

 Download the installation guide



RAYPA

www.raypa.com

Avinguda del Vallès, 322
08227 Terrassa (Barcelona) Spain

